STANCE E+ 0

SPECS

HYBRID SYKKEL TEKNOLOGI	
MOTOR	Giant SyncDrive Pro3X 100Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Dash 2, Smart Assist automatic mode, 5 support levels
DISPLAY	Giant RideControl Dash 2, full color LCD display
BATTERI	Giant EnergyPak 800Wh
CHARGER	Giant EnergyPak 4A smart charger
RAMME	
STØRRELSE	S, M, L, XL
RAMME	ALUXX SL-grade aluminum, 140mm travel FlexPoint linkage driven suspension system, 148x12 Boost rear axle, UDHTM Universal Derailleur hanger, KSA40 compatible, 185x52.5mm shock, 1.5~1.8" headset (ZS62/ZS72)
GAFFEL	Fox 36 Rhythm Air, 150mm travel, Grip damper 110x15mm thru-axle
DEMPER	Fox Float X, 185x52.5mm Sag recommendation: 30% (15.75mm)
KOMPONENTER	
STYRE	Giant Connect TR35, 20mm Rise, 35x760mm [S], 35x780mm [M-XL]
GRIPS	Giant Tactal Pro single lock-on
STYRSTEM	Giant Contact SL 35
SETEPINNE	Giant Contact Switch AT travel adjust dropper seatpost (S:110~140mm, M:140~170m, L/XL: 170~200mm)
SADEL	Giant Contact Ergo Trail
PEDALER	Large platform pedal, 28-pins, PP cage, Steel axle
DRIVVERK	
GIRHENDLER	Shimano Cues LinkGlide
BAKGIR	Shimano Deore XT 11-speed Shadow+
BREMSER	Shimano Deore XT, BR-M8120, hydraulic disc 4-piston, 220mm [F] 203mm [R]
BREMSEHENDLER	Shimano Deore XT BL-M8100
KASSETT	Shimano Cues LinkGlide, 11-speed, 11-50T
KJEDE	Shimano LinkGlide
KRANK	Forged aluminum crank arms

HJUL	
FELG	Giant TRA2, Tubeless ready, 30mm inner width
NAV	Giant E-Drive 260Nm, 72T engagement, e-bike optimized, sealed bearing, Boost Thru-axle 110x15 [F] 148x12mm [R]
EIKE	Sapim Race
DEKK	Maxxis Minion DHF 29X2.50"" WT Foldable, TLR, EXO, 3C Maxx Terra [F] Maxxis Dissector 29X2.40"" WT Foldable TLR EXO+ [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
TILBEHØR	
LÅS	Torx 25 Battery Lock with built-in Torque limiter
SKJERMER/KJEDEBESKYTTER	MRP 1x HD guide, CS e-Mount, 32~38T Adjustable
LIMITS	
MAX CHAINRING SIZE	Direct-mount steel 36T (maximum: 38T)

GEOMETRI

RAMME	S	M	L	XL
Seat Tube Length (mm)	400	425	450	475
Seat Post Insertion Depth (mm)	235	260	285	310
Seat Tube Angle	76,5°	76,5°	76,5°	76,5°
Top Tube Length (mm)	579	606	635	663
Head Tube Length (mm)	100	115	130	145
Head Tube Angle	64,5°	64,5°	64,5°	64,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	132	132	132	132
Wheelbase (mm)	1229	1259	1291	1322
Chain Stay Length (mm)	468	468	468	468
Bottom Bracket Drop (mm)	26	26	26	26
Stack (mm)	614	628	641	655
Reach (mm)	431	455	480	505
Stand Over Height (mm)	746	744	756	762
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	40	40	40	40
Crank Length (mm)	165	165	165	165
Wheel Size	29"	29"	29"	29"

Alle spesifikasjonene kan endres uten varsel.